


AME01HD10
Schottky Barrier Diodes
100V, 1A

Feature


- Low I_R
- High Recovery Speed
- RoHS:Yes
- Based on AEC-Q101

OUTLINE

Package (House Name): SOD-128



Equivalent circuit



Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings	Unit
Storage temperature	Tstg		-55 to 150	°C
Junction temperature	Tj		-55 to 150	°C
Repetitive peak reverse voltage	V _{RRM}		100	V
Average forward current	I _{F(AV)}	Tl=126°C	1	A
Average forward current	I _{F(AV)}		1.57	A
Surge forward current	I _{FSM}	50Hz half sine wave, 1 cycle, Non-repetitive	20	A



※ :See the original Specifications

Electrical Characteristics


Item	Symbol	Conditions	Ratings			Unit
			MIN	TYP	MAX	
Forward voltage	V _F	IF=1A, Tj=25°C	-	-	0.85	V
Reverse current	I _R	VR=VRRM, Tj=25°C	-	-	0.05	mA
Thermal resistance	Rth(j-l)	Junction to lead	-	-	17	°C/W
Thermal resistance	Rth(j-a)	Junction to ambient (P.C.Board mounted)	-	-	80	°C/W

※ :See the original Specifications

順電壓特性
FORWARD CURRENT VS. VOLTAGE




平均順電力損失特性
AVERAGE FORWARD POWER DISSIPATION





ピーク逆電流 — ピーク逆電圧特性
PEAK REVERSE CURRENT VS. PEAK REVERSE VOLTAGE

$T_j = 150^\circ\text{C}$



平均逆電力損失
AVERAGE REVERSE POWER DISSIPATION







平均順電流－リード温度定格
AVERAGE FORWARD CURRENT VS. LEAD TEMPERATURE

$V_{RM}=50V$

AME01HD10

平均順電流
(A)




平均順電流－周囲温度定格
AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE

Glass-Epoxy Substrate Mounted (Soldering Land=2×2mm, Both side), $V_{RM}=50V$

AME01HD10

平均順電流
(A)



サージ順電流定格 SURGE CURRENT RATINGS


f=50Hz, Half Sine Wave, Non-Repetitive, No Load

AME01HD10

サ
ー
ジ
順
電
流

(A)

SURGE FORWARD CURRENT (A)



接合容量特性 JUNCTION CAPACITANCE VS. REVERSE VOLTAGE


Tj=25°C, Vm=20mV_{RMS}, f=100kHz, Typical Value

AME01HD10

接
合
容
量


(pF)

JUNCTION CAPACITANCE (pF)




SMA_FL


■外形図 Package Outline



■推奨ランドサイズ Mounting Pad Layout



■内部回路図 Inner Circuit



1. If you wish to use any such product, please be sure to refer to the specifications issued by Shindengen.
2. All products described or contained herein are designed with a quality level intended for use in standard applications requiring an ordinary level of reliability. If these products are to be used in equipment or devices for special or specific applications requiring an extremely high grade of quality or reliability in which failures or malfunctions of products may directly affect human life or health, a local Shindengen office must be contacted in advance to confirm that the intended use of the product is appropriate. Shindengen products are grouped into the following three applications according to the quality grade.
 - 【Standard applications】
Computers, office automation and other office equipment, communication terminals, test and measurement equipment, audio/visual equipment, amusement equipment, consumer electronics, machine tools, personal electronic equipment, industrial equipment, etc.
 - 【Special applications】
Transportation equipment (vehicles, ships, etc.), trunk-line communication equipment, traffic signal control systems, anti-disaster/crime systems, safety equipment, medical equipment, etc.
 - 【Specific applications】
Nuclear reactor control systems, aircraft, aerospace equipment, submarine repeaters, life support equipment and systems, etc.
3. Although Shindengen continuously endeavors to enhance the quality and reliability of its products, customers are advised to consider and take safety measures in their design, such as redundancy, fire containment and anti-failure, so that personal injury, fires, or societal damages can be prevented.
4. Please note that all information described or contained herein is subject to change without notice due to product upgrades and other reasons. When buying Shindengen products, please contact the Company's offices or distributors to obtain the latest information.
5. Shindengen shall not bear any responsibility with regards to damages or infringement of any third-party patent rights and other intellectual property rights incurred due to the use of information on this website.
6. The information and materials on this website neither warrant the use of Shindengen's or any third party's patent rights and other intellectual property rights, nor grant license to such rights.
7. In the event that any product described or contained herein falls under the category of strategic products controlled under the Foreign Exchange and Foreign Trade Control Law of Japan, exporting of such products shall require an export license from the Japanese government in accordance with the above law.
8. No reprinting or reproduction of the materials on this website, either in whole or in part, is permitted without proper authorization from Shindengen.